

# Tape Solutions for Heat Sealing



# Tape Solutions for Heat Sealing

ATS offers a complete range of **CHR**® PTFE Adhesive Tapes to perform in a variety of heat seal packaging processes involving impulse heat sealers and hot bar sealers. **CHR** heat sealing tapes provide a non-stick, abrasion resistant surface designed for use in high temperature heat sealing applications. These highly durable tapes allow for increased process speeds and minimal down time increasing overall process efficiency. Different backings and adhesive systems are combined to offer a variety of solutions that balance cost and performance.

## Heat Sealing Tapes

**Products:** PTFE Glass Laminate Tape, PTFE Glass Cloth Tape, Zone Tape, Extruded PTFE Tape, Enhanced High Modulus PTFE Tape, Filled PTFE Tape

**Function:** Release surface for packaging plastics

**Features:** Non-stick surface, wear resistance, temperature resistance, dimensional stability, PTFE Glass Cloth for tear resistance

**PTFE Glass Laminate Tape:** CHR SGB6 and SGC6 Chemlam® are premium solutions for heat seal packaging. A proprietary manufacturing method allows these products to have fewer defects such as cracks and pinholes. The more consistent release surface and higher PTFE thickness over the glass gives these products longer life and more cycles compared to lower grade options. This allows users to operate more efficiently with less down time spent changing release tapes.

**PTFE Glass Cloth Tape:** PTFE is coated onto glass fabric to enhance dimensional stability, tear strength, and abrasion resistance while maintaining a non-stick surface. Several different grades are available at various PTFE coating weights to offer economic options or high performance solutions for smoother seals and increased durability. CHR SG25 series is the most commonly used solution because it offers a balance between cost and performance. In addition to silicone adhesive, acrylic is available for application temperatures under 350°F where higher bond strength is desired.

**Aluminum PTFE Foil Tape:** CHR MD15 is PTFE laminated to aluminum foil. The lamination construction gives the tape longer life in application and can be run at faster speeds due to improved thermal conductivity. The metal construction can be detected by X-ray and metal detectors on food packaging lines that detect foreign contamination.

**Zone Tape:** CHR 2829 is made from PTFE coated glass fabric with selective adhesive placement. Adhesive can be placed only where needed to keep it away from the heating element for hot wire sealers.

**Extruded PTFE Tape:** These tapes are made of 100% extruded PTFE film backing. The additional PTFE content compared to glass reinforced products allows for extended life in narrow heat sealing applications where dimensional stability is not as critical. CHR 2275, 2283, and 2285 are brightly colored products that can be seen clearly against the metal platen they are adhered to. CHR 2283 is an acrylic adhesive option for lower temperature heat sealing processes (<350°F). The 2 mil thickness of these products improves heat transfer allowing for faster line speeds.

**High Modulus PTFE Tape:** CHR R233 and R253 are made with 3 mil high modulus PTFE films. The increased PTFE backing thickness increases longevity over thinner extruded tape options. CHR R233 has an acrylic adhesive system for higher adhesive strength while CHR R253 is designed for use in higher temperature heat sealing processes. CHR 22B5-2 and 22B5-2HA are made with a 2.2 mil anti-static high modulus backing. The substrate is designed for abrasion resistance needed for heat sealing and roller wrap applications. CHR 22B5-2 resists movement in high shear PE extrusion applications and 22B5-2HA offers high adhesion desired in heat sealing to prevent edge curl.

**Filled PTFE Tape:** CHR Rulon® Tape will last the longest as a release surface in heat sealing processes compared to the rest of the CHR tape portfolio. It is made from a thick PTFE backing that contains special fillers designed to maximize abrasion resistance and product life. CHR RU and RU101 can last up to 20 times as long as standard PTFE glass heat seal tapes saving both time and money from improved process efficiency.

# Heat Sealing Tapes

Backing Material	Substrate Grade	Adhesive	Tape Backing Thickness							Operating Temperature °F(°C)	Product Features	
			Product Code									
			0.002in (0.050mm)	0.003in (0.076mm)	0.004in (0.102mm)	0.005in (0.127mm)	0.006in (0.152mm)	0.008in (0.203mm)	0.010in (0.254mm)			0.014in (0.356mm)
PTFE Glass Cloth Laminate	<b>Chemlam</b>	Silicone			SGB6-4		SGC6-6		SGB6-10		-100 to 500 (-73 to 260)	<b>Chemlam</b> backing for maximum life
PTFE Aluminum		Silicone		MD15							-100 to 500 (-73 to 260)	Metal detectable
PTFE Glass Cloth	High Performance	Silicone		A2005							-100 to 500 (-73 to 260)	High temperature adhesion
PTFE Glass Cloth	High Performance	Silicone				SG16-05					-100 to 500 (-73 to 260)	High performance, long life & clean release adhesive
PTFE Glass Cloth	High Performance	Silicone		SG15-03		SG15-05	SG15-06			SG15-14	-100 to 500 (-73 to 260)	High performance, long life
PTFE Glass Cloth	Premium	Acrylic		SG03-03							-40 to 350 (-40 to 177)	Premium, long life & high adhesion
PTFE Glass Cloth	Premium	Silicone		SG05-03		SG05-05	SG05-06		SG05-10		-100 to 500 (-73 to 260)	Premium & long life
PTFE Glass Cloth	Primary	Acrylic				SG23-05			SG23-10		-40 to 350 (-40 to 177)	Balanced life, cost & high adhesion
PTFE Glass Cloth	Primary	Silicone		SG26-03		SG26-05					-100 to 500 (-73 to 260)	Balanced life, cost & clean release adhesive
PTFE Glass Cloth	Primary	Silicone		SG25-03		SG25-05	SG25-06		SG25-10		-100 to 500 (-73 to 260)	Balanced life & cost
PTFE Glass Cloth	Industrial	Silicone		SG35-03		SG35-05	SG35-06		SG35-10		-100 to 500 (-73 to 260)	Economical grade
PTFE Glass Cloth		Acrylic		2829-03		2829-05					-40 to 350 (-40 to 177)	Zone tapes with selective adhesive placement
Extruded PTFE		Acrylic	2283-2								-40 to 350 (-40 to 177)	High adhesion & high heat transfer & easy to detect wear
Extruded PTFE		Silicone	2265-2, 2275-2, 2285-2								-100 to 500 (-73 to 260)	High heat transfer & easy to detect wear
High Modulus		Silicone	22B5-2								-100 to 500 (-73 to 260)	Resists movement, designed for roller wrap applications & anti-static
High Modulus		Silicone	22B5-2HA								-100 to 500 (-73 to 260)	High adhesion & anti-static
Enhanced High Modulus PTFE		Acrylic		R233							-40 to 350 (-40 to 177)	High adhesion & thick PTFE layer
Enhanced High Modulus PTFE		Silicone		R253							-100 to 500 (-73 to 260)	Thick PTFE layer
Filled PTFE		Acrylic						RU101			-40 to 350 (-40 to 177)	High wear resistance & high adhesion
Filled PTFE		Silicone						RU			-100 to 500 (-73 to 260)	High wear resistance

# *Your Partner* **in Custom Tape Solutions**

Advanced Technology Supply, Inc. is an award-winning Converter, Fabricator, and Distributor of Pressure Sensitive Tapes, Elastomers, Plastic Films, Coated Fabrics, and Composite Fabrics. Our Florida-based business spans almost 40 years and we are an industry leader with a flawless reputation, supplying mil-spec tape and mil-spec rubber products to the military, aerospace, electrical, construction, and packaging industries throughout the world.

We offer precision engineering capabilities including Cutting, Slitting, and Fabrication and we are authorized converters and distributors for some of the biggest brands in the industry such as 3M, Saint-Gobain, and many more.

We have an unwavering commitment to upholding the highest standards and this is mirrored by our continued compliance with ISO 9001 and other industry standards. We are also ANAB Accredited.

We welcome custom orders and our premium service is designed to tailor to your exact specifications.

**ATS is an authorized converter and distributor of Saint Gobain.**

The logo for Advanced Technology Solutions, Inc. (ATS) features the letters 'ATS' in a bold, metallic, sans-serif font. The letters have a 3D effect with highlights and shadows, giving them a brushed metal appearance. They are set against a dark blue background.

Advanced Technology Solutions, Inc

[www.ats24.com](http://www.ats24.com)



1001 W. Newport Center  
Drive Deerfield Beach,  
FL 33442



[sales@ats.com](mailto:sales@ats.com)



800.793.6307  
407.880.2022



Mon - Fri: 9:00 - 18:00  
Sat - Sun: Closed

Scan to go to our website

